



Built for performance

PSR Dual Sport Kickstand Installation Instructions 08-04510-29 / DK11

Parts List: Kickstand with M8X20 bolt; M8x25 bolt; clamp piece

****Removable Thread Locking Compound is recommended on all bolt threads****

1. Verify bike model & kickstand application before installation!
2. Place bike securely on a center stand; Remove frame protection plastic frame cover on the left side of the bike.





3. Remove the stock kickstand
4. Using supplied M8x25 bolt, insert thru the bottom bolt hole on the kickstand base.
5. Install M8x20 bolt to the top of the kickstand bracket with the included clamp piece to the bike; Tighten fully
6. Tighten bolt in Step 4.
7. Cut the enclosed template by following the Template Cut Line
8. Using the template, tape it to the plastic piece from Step 2 by lining up the edges of the template with edges of the plastic.
9. Mark and trim the plastic frame cover using the Cut Line on the template. Depending on user preference, some adjustments on trimming maybe necessary for the plastic frame cover to fit around the kickstand.
10. Reinstall the plastic frame cover; It will flex slightly with PSR kickstand installed.
11. Rotate kickstand through its entire travel and check for clearance prior to use.

Usage & Maintenance of PSR Dual Sport Kickstand:

1. Check all hardwares for tightness before each ride.
2. Do Not Start the bike with kickstand down.
3. Do Not Kickstart the bike with kickstand down.
4. Clean and lubricate the kickstand pivot area after each ride.

Professional installation is recommended. Always use proper safety measures during the install of this product. Do not try to install this product without proper tools, recently calibrated torque wrench, correct torque specifications from factory service manual, safety goggles and gloves. The motorcycle must be in a fixed secure position before the install process begins. PSR is not responsible for any losses, damages or claims resulting from injuries sustained or alleges to have been sustained by the installation of this product not installed by a certified mechanic experienced in the installation of component parts on motorcycles. PSR is not responsible for the functionality of the product not properly installed or under circumstances in which there has been a modification to the product by any person not employed by PSR.



Scale check